



**Information for reference only.  
Contact us for detailed proposal**

### TVLA-A

Model	TLV-200A	TLV-300A	TLV-400A	TLV-500A	TLV-600A	TLV-700A
<b>Max. Coil Width</b>	200mm	300mm	400mm	500mm	600mm	700mm
<b>Strip Thickness</b>	0.5-3.2mm					
<b>Pinch Rolls</b>	1 pair (Ø72mm), manual					
<b>Straightening Rolls</b>	3 over 4 (Ø60mm), upper rolls mounted in a bank					
<b>Feed Rolls</b>	1 pair (Ø72mm), sprung					
<b>Motor Size</b>	0.75kW	1.5kW		2.2kW		
<b>Speed (Variable)</b>	15m/min max.					
<b>Control</b>	Touch Stand					

### TVLA-H

Model	TLV-200H	TLV-300H	TLV-400H	TLV-500H	TLV-600H	TLV-700H
<b>Max. Coil Width</b>	200mm	300mm	400mm	500mm	600mm	700mm
<b>Strip Thickness</b>	0.6-4.5mm					
<b>Pinch Rolls</b>	1 pair (Ø72mm), manual					
<b>Straightening Rolls</b>	3 over 4 (Ø72mm), upper rolls mounted in a bank					
<b>Feed Rolls</b>	1 pair (Ø72mm), sprung					
<b>Motor Size</b>	1.5kW	2.2kW		3.75kW		
<b>Speed (Variable)</b>	15m/min max.					
<b>Control</b>	Touch Stand					

